

www.dakotamicro.com

# Digital Speed Dome Cameras

These current, state-of-the-art Day/Night superior speed dome cameras include Digital Signal Processing (DSP) to provide enhanced clarity, color and detail in well lit, or low light applications. Available in 220x or 270x Zoom.

## FEATURES:

- ◆ 22x/27x optical zoom is combined with 10x digital magnifier, providing a total of 220x/270x zoom
- ◆ Advanced Sony DSP Super HAD CCD Camera
- ◆ D-MAX, RS-485 and RS-422 controllable, makes for fast and easy integration with existing systems
- ◆ Up to 6 programmable privacy zones
- ◆ Adjust white balance manually or via Automatic Tracing White Balance (ATW)
- ◆ Choose Auto or manual gain control to for low light conditions with zoom position, even at max magnification
- ◆ Dual fan and heater allows dome to be used in extreme temperature conditions (outdoor version only)



- ◆ Ability to "flip" 180 deg when camera tilts to lower limits manually or automatically
- ◆ Dome supports PTZ trace pattern or "tour"
- ◆ Pre-programmed default spiral "apple peel" pattern to cover entire area
- ◆ 128 Presets when used with accessory PTZ keyboard
- ◆ Alarms processed internally OR externally
- ◆ Supports 2400 bps, 4800bps and 9600bps baud rates
- ◆ Dome will resume "Home position" after user defined inactive period.
- ◆ User defined line-lock to prevent vertical rolling in multi camera applications
- ◆ Vertical sync phase of power when line-lock is enabled, making it ideal for single and multi-phase power installations surge protection for both video and power connections
- ◆ Built in protection against irregular input voltage
- ◆ Aluminum construction and vandal resistand bubble, IP66 rated (outdoor version only)
- ◆ Meet CE and FCC criteria
- ◆ Continuous autofocus with one-shot and manual override

COMMERCIAL

INDUSTRIAL

GOVERNMENT

RESIDENTIAL



